

# data sheet

## PMPH200

## PMPH203

## PMPH216

## PMPH230

# PERIMax


## pump series™

### Replacement Pump Heads



Important: All Series 200 (including 203, 216 and 230) peristaltic pumps are supplied with sealed pump heads and the tube cannot be changed. When the performance of the tube set or pump head has declined, the complete pump head can easily be replaced. We are able to supply pump heads unsealed for customers that wish to change the tubing periodically. Please contact us for details.

- Low cost solution for light duty dispensing and metering
- 9 tubing materials in stock to match your application
- Compatible with many chemicals and aggressive fluids
- Pump head is factory sealed/welded
- Fluid only contacts the inside of the tubing
- Weight 1.5 ounces
- Dimensions: 3.500 x 2.375 x 1.125 inches



# Simply Pumps™ SimplyPumps.com

## 724-864-5959

Specifications are subject to change without notice. No liability or warranty implied by this information.  
Copyright © 2018 Simply Pumps Revised 9/14/18 R3

# data sheet



## PMPH200

## PMPH203 PMPH216 PMPH230

### Replacement Pump Head Part Numbers

Stock Tubing Materials	200	203	216	232	233	235
Norprene® Food Process A-60F	PMPH200F	PMPH203F	PMPH216F	PMPH232F	NA	NA
Norprene® Industrial Grade A-60G	PMPH200N	PMPH203N	PMPH216N	NA	NA	NA
Norprene® Chemical	NA	PMPH203C	NA	NA	NA	NA
Tygon® Fuel and Lubricant F-4040-A	NA	PMPH203T	NA	NA	NA	NA
Tygotprene® XL-60	PMPH200G	PMPH203G	NA	NA	NA	NA
Tygon® Long Flexible Life	PMPH200E	PMPH203E	NA	NA	NA	NA
Tygon S3™ E-3603 Laboratory	PMPH200L	PMPH203L	NA	NA	PMPH233L	PMPH235L
Versilic® Silicone SPX-50	PMPH200S	PMPH203S	PMPH216S	NA	NA	NA
Soft Viton® High Temperature	PMPH200V	PMPH203V	PMPH216V	NA	NA	NA
<b>Sealed replacement 200 series pump heads with tubing installed</b>	<b>3/16 x 5/16</b>	<b>1/8 x 1/4</b>	<b>1/16 x 3/16</b>	<b>1/32 x 5/32</b>	<b>3/32 x 7/32</b>	<b>5/32 x 9/32</b>

**Tubing ID x OD**

Stock Tubing Materials	Simply Pumps Suffix	Durometer Rating	Temperature Range °F		Coupler Material
			Low	High	
Norprene® Food Process A-60F	F	61	-75	275	Polypropylene
Norprene® Industrial Grade A-60G	N	61	-75	275	Polypropylene
Norprene® Chemical	C	61	-75	165	PVDF (Kynar)
Prothane II™	P	70	-35	175	PVDF (Kynar)
Tygon® Fuel and Lubricant F-4040-A	T	57	0	165	Polypropylene
Tygotprene® XL-60	G	60	-87	250	Polypropylene
Tygon® Long Flexible Life	E	56	-51	165	Polypropylene
Tygon S3™ E-3603 Laboratory	L	56	-51	165	Polypropylene
Versilic® Silicone SPX-50	S	50	-75	350	Polypropylene
Soft Viton® High Temperature	V	60	-25	400	PVDF (Kynar)
Vytex™ Clear Polyvinyl	Y	60	-60	160	Polypropylene

Norprene, Tygon, Tygotprene, and Versilic are registered trademarks of Saint-Gobain Performance Plastics. Viton is a registered trademark of DuPont Performance Elastomers LLC. Vytex and Prothane II are trademarks of Randolph Austin Company

# Simply Pumps.com

## 724-864-5959

Specifications are subject to change without notice. No liability or warranty implied by this information.  
 Copyright © 2018 Simply Pumps Revised 9/14/18 R3